



The Power of IP to Enhance Business Communications

Take enterprise-wide communication to a whole new level with an IP communication system that integrates your voice, data networking, and application solutions. One that combines the advantages of network-based telephony and the features of PBX systems, as well as valuable options like Voice Mail/Auto Attendant/Unified Messaging, Automatic Call Distribution, Strata Net multiple system networking, FeatureFlex®

adaptability/customization tools, and more to improve your business' overall productivity and customer service.

Strata® CIX™ systems are designed to work exactly as you need today, in one or multiple locations, while enabling you to grow and add other capabilities in the future. The Strata CIX is the ultimate, modular, scalable, networkable communication system for your business.

SPECIFICATIONS

Model	Strata CIX200								
Capacities	96 trunks or 160 endpoints and combinations up to 192 total.								
Chassis	Base Cabinet				Expansion Cabinet				
Measurements	Width	Height	Depth	Weight	Width	Height	Depth	Weight	
<i>Metric</i>	440 mm without bracket 483 mm with bracket	89 mm	410 mm	7.2 kg	440 mm without cabinet 483 mm with bracket	89 mm	410 mm	7.2 kg	
<i>English</i>	17.3 in. without bracket 19 in. with bracket	3.5 in.	16.1 in.	16 lbs.	17.3 in. without bracket 19 in. with bracket	3.5 in.	16.1 in.	16 lbs.	
Power Supply Unit (PSU)	Initially Built-in (one per cabinet).								
Primary AC Power	Input AC 120VAC, 4.0 amps maximum. AC Frequency Single-phase (45Hz - 65Hz). 480 watts per cabinet (maximum).								
Power Backup	An Uninterruptible Power Supply (UPS) is required for power backup on a CIX200. The UPS is similar to the ones used for computer systems and networking equipment.								
Chassis Installation	19" Rack-mount (preferred) or Table top. Standard 19" rack-mounting, IEC297-1 (EIA RS 310-D), 465.1mm (front face screw pitch-width).								
Compliance	Safety: UL EMC: FCC Part 15 Class A (Subpart A) HAC and Volume Control: FCC Part 68 Network safety: TIA-968-2-A								
FCC Registration	PBX: CJ6PF03BDTCHS192 Hybrid: CJ6MF03BDTCHS192 Key: CJ6KD03BDTCHS192								
Operating Temperature	32~104° F (0~40° C)								
Operating Humidity	20~80% Relative humidity without condensation								
Storage Temperature	-4~140° F (-20~60° C)								
Voice Mail Compatibility	Strata Media Application Server, Stratagy® ES, iES32, iES16, IVP8								

SPECIFICATIONS

Trunk Compatibility	Analog: Loop or ground start, DID, E&M Digital: T1, ISDN PRI and BRI IP: Strata Net IP Networking, SIP Trunking E911: CAMA and ISDN PRI
IP Telephone Compatibility	Toshiba IP5000-Series MEGACO+ models: <ul style="list-style-type: none"> > IP5022-SD full-duplex speakerphone with 10 programmable buttons and 4-line x 24-character LCD. > IP5122-SD full-duplex speakerphone with 10 programmable buttons and 4-line x 24-character Backlit LCD with contrast adjustment. > IP5122-SDC full-duplex speakerphone with 10 programmable buttons and 4-line x 24-character Backlit LCD with contrast adjustment and analog CO line interface. > IP5132-SD full-duplex speakerphone with 20 programmable buttons and 4-line x 24-character Backlit LCD with contrast adjustment. > IP5131-SDL full-duplex speakerphone with 10 programmable buttons and LCD key labels and 4-line x 24-character Backlit LCD with contrast adjustment. <p>802.3af Power-over-Ethernet compliant. Gigabit Ethernet switch for PC connection to your IP Network. 802.1Q Virtual Local Area Network (VLAN) compliant. Hitachi WIP5000E-A Wireless SIP Telephone.</p>
Digital Telephone Compatibility	Toshiba DP5000-Series models: <ul style="list-style-type: none"> > DP5008 single-line telephone with one programmable button. > DP5018-S speakerphone with 10 programmable buttons. > DP5022-SD speakerphone with 10 programmable buttons and 4-line x 24-character LCD with contrast adjustment. > DP5122-SD speakerphone with 10 programmable buttons and 4-line x 24-character Backlit LCD with contrast adjustment. > DP5032-SD speakerphone with 20 programmable buttons and 4-line x 24-character LCD with contrast adjustment. > DP5132-SD speakerphone with 20 programmable buttons and 4-line x 24-character Backlit LCD with contrast adjustment. > DP5130-SDL speakerphone with 10 programmable LCD-label buttons and 4-line x 24-character Backlit LCD with contrast adjustment.
Analog Device Compatibility	Dealer-supplied standard telephones with or without Caller ID, FAX machines, modems, etc.
Answer Position Options	LM5110 Add-On Module with 10 programmable Backlit LCD-label buttons. KM5020 Add-On Module with 20 programmable buttons. IDM5060 and DDM5060 DSS/BLF Console with 60 programmable buttons. Strata PC Attendant Console.
User Mobility Options	uMobility dual-mode smartphones via W-Fi and cellular networks. SoftIPT® soft phone client on laptop or tablet PC via Wi-Fi Wireless LAN or Internet. SoftIPT soft phone client on PDA via Wi-Fi Wireless LAN. Wireless IP telephone support via Wi-Fi Wireless LAN. Cordless digital telephone.
System Administration	Browser-based unified administration of PBX and voice mail functions. Network eManager® centralized installation/maintenance of all Strata CIX systems for technicians and administrators. eMonitor monitoring of alarm conditions from multiple Strata CIX systems. My Phone Manager® personal administration for individual users. Traffic measurement reports stored on local SD flash memory card.
Standard System Features	Over 300 standard telephony features to provide the functionality you need.
Advanced Application Options	Add valuable options like Voice Mail/Auto Attendant, Unified Messaging, Fax Integration, Automated Speech Recognition, Text-To-Speech, Interactive Voice Response, Automatic Call Distribution and Reporting, Voice Over Internet Protocol, Strata Net multiple system networking, Info Manager® Web-based telephone applications, FeatureFlex adaptability/customization tools, uniform call distribution, centralized network SMDR, and more.
Multi-system Networking	Strata Net networking of up to 128 nodes via IP or ISDN PRI.
Feature Customization	FeatureFlex adaptability tools for feature creation/customization.

Toshiba America Information Systems, Inc., Telecommunication Systems Division

9740 Irvine Blvd., Irvine, CA 92618-1697 www.telecom.toshiba.com

To locate an Authorized Dealer, call: (800) 222-5805

© 2010 Toshiba America Information Systems, Inc. All product, service and company names are trademarks, registered trademarks or service marks of their respective owners. Information including without limitation specifications, availability, content of services, and contact information is subject to change without notice.

Literature Order #: TSD-CIX-BR-200-DS-VF/4500146

