

Perfect Voice Pinnacle -Blade Platform



System Compatibility Reference Chart

Switch	S/W Level Required	Emulation Supported: RSTU, BSLU	Integration Supported: S=Serial SMDI L=LAN SMDI I=Inband Signaling	Maximum Number of Ports Supported
DK16e	3.2 or higher	RSTU	S,I	8
DK40	R4.X	RSTU	S,I	8
DK40i	R4.X	RSTU	S,I	8
DK280	3.2 or higher	RSTU	S,I	8
DK424	3.2 or higher	RSTU	S,I	8
DK424i	R4.X	RSTU	S,I	8
CTX28	Not Supported	Not Supported	Not Supported	Not Supported
CIX40	Not Supported	Not Supported	Not Supported	Not Supported
CTX/CIX 100/200/670 ¹	R1.0 through 4.0	RSTU	S,I	8
CTX/CIX 100/200/670 ¹	R4.1 and higher	RSTU, BSLU/BSLS	S,I	16 ²
CTX/CIX 100/200/670/1200 ¹	R5.0 and higher	RSTU, BSLU/BSLS	S,L,I	16 ²

¹ Softkeys and Call Record Require SMDI Integration

² Requires slot programmed as BSLU/BSLS to Achieve 16 Port Capacity (R4.1 and higher)



430 Woodruff Road, Suite 300
Greenville, SC 29607
864.297.4401 www.teleco.com